


N series



182 N-type Bifacial Module

575W ~ 595W

 **12** years product workmanship warranty

 **30** years linear power output warranty

 **1%** 1st-year degradation
0.40% annual degradation



 Conventional  LESSO Solar Module

FEATURES AND BENEFITS



Topcon technology, higher power generation.



High density packaging, improving energy density.



Even cloudy or foggy days, better weak illumination response.



Zero LID, increase power generation.



Better temperature coefficient, more power generation.



Higher power output, lower bos cost.



Multiple weather, resistance tests, wider applicability.



Double-sided generation, powerfully energy boost.

LESSO 182 N-type Bifacial Module (72)



Power Range
575W ~ 595W




Power Output Tolerance
0W ~ +5W



Maximum Efficiency
23.03%

Structure Performance

Solar Cell Type	182mm N-TOPCon Mono Cell (Half Cell)
Solar Cell Arrangement	144pcs(6×24)
Module Dimension	2278×1134×35mm/30mm
Weight	32.3kg(35mm) / 31.2kg(30mm)
Front Glass	2.0mm, highly transparent tempered glass with anti-reflective coating
Frame	Anodized Aluminum Alloy / Polyurethane Composite Frame
Junction Box	IP68 rated
Cable	4mm ² , portrait ^{400mm(+)} / _{200mm(-)} , landscape ^{1400mm(+)} / _{1400mm(-)} Length can be customized
Diode Quantity	3 pcs
Front side / Rear side	5400pa / 2400pa
Connector	MC4 Compatible
Per Pallet	31pcs(35mm) / 36pcs(30mm)
Per Container(40'HQ)	620pcs(35mm) / 720pcs(30mm)




Electrical Performance Parameters

Model Type	575C(HBD)72(182)		580C(HBD)72(182)		585C(HBD)72(182)		590C(HBD)72(182)		595C(HBD)72(182)		
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	
Nominal Max. Power	P_{MAX} (W)	575	433	580	437	585	441	590	445	595	449
Max. Power Voltage	V_{MP} (V)	42.60	40.02	42.75	40.17	42.89	40.32	43.04	40.47	43.19	40.62
Max. Power Current	I_{MP} (A)	13.50	10.82	13.57	10.88	13.64	10.94	13.71	11.00	13.78	11.06
Open Circuit Voltage	V_{OC} (V)	51.23	48.66	51.43	48.85	51.63	49.04	51.83	49.23	52.03	49.42
Short Circuit Current	I_{SC} (A)	14.27	11.51	14.33	11.56	14.39	11.61	14.45	11.66	14.51	11.70
Module Efficiency	(%)	22.26		22.45		22.65		22.84		23.03	

* STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5; NMOT: Irradiance 800W/m², Ambient Temperature 20°C, Air Mass AM1.5, Wind Speed 1m/s; Power measurement tolerance ±3%.

Current-Voltage & Power-Voltage Curve (595C)



Bifacial Output-rearside Power Gain

Gain	Maximum Power		P_{MAX} (W)				
		P_{MAX} (W)	604	609	614	620	625
5%	Maximum Power	P_{MAX} (W)	604	609	614	620	625
	Module Efficiency	(%)	23.37%	23.57%	23.78%	23.98%	24.18%
10%	Maximum Power	P_{MAX} (W)	633	638	644	649	655
	Module Efficiency	(%)	24.48%	24.70%	24.91%	25.12%	25.34%
25%	Maximum Power	P_{MAX} (W)	719	725	731	738	744
	Module Efficiency	(%)	27.82%	28.07%	28.31%	28.55%	28.79%

Temperature Characteristics

Nominal Module Operating Temperature	44±2°C	Temperature Coefficient (V_{OC})	-0.25%
Temperature Coefficient (I_{SC})	+0.043%	Temperature Coefficient (P_{MAX})	-0.30%

Maximum Parameters

Working Temperature	-40~+85°C
Maximum System Voltage	1500V DC
Nominal Maximum Fuse Current	30A