

# LESSO



## AC Charger

### Features

7/11/22kW Compatible designs

Home use with intelligent APP control

High protection for complex environment

Smart light information

Minimal size, stream line design

Smart charging and load balancing

6mA DC residual current protection

### Applications

Home / Shopping mall / Public parking

Model	LSACS-E -32/230	LSACS-U -32/230	LSACS-U -50/230	LSACS-E -16/400	LSACS-E -32/400
Rated power	7kW	7kW	11kW	11kW	22kW
Voltage	220~240VAC			380~415VAC	
Power supply	P+N+PE			3P+N+PE	
Current	32A	32A	50A	16A	32A
Frequency	50/60Hz				
Charge plug	Type2	Type1	Type1	Type2	Type2
Cable length	3/5m (include connector)				
Enclosure	ABS+PC(MR technology)				
LED indicator	Green/Yellow/Blue/Red				
LCD display	4.3"color LCD (Optional)				
RFID	Non-contact(ISO/IEC14443 A)				
Start method	QR code/Card/BLE5.0/PnC				
Interface	BLE5.0/RS485, Ethernet/4G/WIFI (Optional)				
Protocol	OCPP1.6J/2.0J(Optional)				
Energy Meter	Onboard Metering,Accuracy level1.0				
Emergency stop	Yes				
RCD	30mA TypeA+6mA DC				
EMC LEVEL	CLASS B				
Protection grade	IP55 and IK08				
Certification	CE,CB,KC				
Standard	EN/IEC 61851-1,EN/IEC 61851-21-2				
Installation	Wall mounted/Floor mounted				
Temperature	-25°C~+55°C				
Humidity	5%~95%				
Atitude	≤2000m				
Product size	218×109×404 (W×D×H,mm)				
Net weight	3.6kg	3.6kg	4.5kg	4.0kg	5.0kg

Remarks: specifications are subject to change without notice