LESSO





AC Charger

Features

Home use with intelligent APP control

High protection for complex environment

Stream line design

Smart charging and load balancing

Applications

Home / Shopping mall / Public parking



Model	LSACS-C-32/220-A01	LSACS-C-32/220-A02	LSACS-C-32/220-Y01	LSACS-C-32/220-Y02
Product Configuration	Home Edition		Operational Edition	
Rated power	7kW			
Output current	32A			
Voltage	220V			
Power supply	Single phase: L1、N、PE			
Plug Type	GB/T			
Start method	Bluetooth/Swipe card	Bluetooth/Swipe card	4G/APP	4G/APP
Telecommunication	Bluetooth	Bluetooth	4G/APP	4G/APP
Charging mode	Auto fill/on time			
Energy Meter	Onboard Metering, Accuracy level 1.0			
Product size	287*176*85mm			
Protection grade	IP55			
Display Mode	LED	4:3 Display	LED	4:3 Display
Installation	Wall mounted/Floor mounted			
Flame Retardant Rating	UL94-V0			
Cable length	5m (customizable)			
Standard	GB/T20234.2-2015, GB/T18487.1-2015			
Temperature	-30°C ~ +85°C			
Humidity	≤90%			
Altitude	<2000m			

Remarks: specifications are subject to change without notice





Guangdong Lesso Energy Storage Technology Co., Ltd